




Aqua Interior /Exterior Dual Primer is a water-based multi purpose primer suitable for application on interior / exterior as a primer coat to interior/exterior emulsion

1. Excellent opacity and whiteness
2. Improves appearance of top coat
3. Does not chalk and can be applied on adequately cured fresh plaster
4. Does not require curing with water
5. Provides excellent adhesion to top coat emulsions
6. Prevents peeling off of top coat emulsions



Shelf life: 3 years from the date of manufacture is original tightly closed containers away from direct sunlight and excessive heat

On smooth primed masonry surface by brushing




Drying Time
30 min

****Actual coverage may vary from the quoted coverage due to factors such as method and condition or application and surface roughness and porosity**



ISO: 9001:2015 (QMS)



Can be used for priming plastered walls, asbestos, brick work, concrete etc.,

Apply an emulsion coat over Exterior Wall Primer.

- a. Drying time: Surface dry time 30 min
- b. Sheen levels: 15-35 at 35 deg GH
- c. Flash point IS101/1987 Part 1. Sec 6: NA
- d. Stability of thinned paint: To be used within 24 hours

- ◆ Do not apply when ambient temperature is less than 10°C or if the temperature might drop is this level within 4 hrs of applications
- ◆ Do not over-thin or over-extend the brush
- ◆ Stir well and strain before use
- ◆ Tinted paints need thorough shaking immediately after stainer addition as well as before use
- ◆ Store the container with the lid tightly closed in an upright position in a cool dry place
- ◆ Keep out of reach of children and away from eatables
- ◆ May be harmful if swallowed. In case of ingestion seek immediate medical attention
- ◆ Wear eye protection during application in case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- ◆ In case of skin contact immediately wash skin with soap and plenty of water Get medical attention if irritation develops or persists.
- ◆ Do not breathe vapor or spray It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- ◆ Do not pour leftover paint down the drain or in water courses.
- ◆ In the event of spills, contain spillage using sand or earth
- ◆ No added Lead. Mercury or Chromium compounds.

AQUA PAINTS & CHEMICALS

214 & 215, JCK Industrial Park, Belagola Industrial Area
KRS Cross Road, Metagalli, Mysuru-570016

