
## **Blossom Acrylic Distemper**



On smooth primed masonry surface



\*\*Actual coverage may vary from the guoted coverage due to factors such as method and condition or application and surface roughness and porosity







ISO: 9001:2015 (QMS)

# Interior )



Agua Paints Blossom Acrylic Distemper is water-based, interior wall paint. It gives walls a smooth and matt finish. Its fortified formulation delivers a combination of good looks and durable performance.

### **Environment friendly:**

Aqua Paints Blossom Acrylic Distemper is based on an acrylic co-polymer formulation. It is environment friendly, contains no added lead, cadmium, mercury or arsenic. Durably It has a high durability with strong antichalking performance

#### **Maintenance**

This product has been specifically formulated such that its finish has a high wet edge time which gives a uniform matt finish.

Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

For removing stains, sponge clean with a mild soap solution followed by wiping with clean water. Ensure a drying time of minimum 4 weeks from application before cleaning

- a) Drying time: Surface dry time 30 min
- b) Flash point IS101/1987 Part 1, Sec 6: Non-flammable
- c)Stability of thinned paint: To be used within 24 hours
- ◆ Do not apply when ambient temperature is less than 10°C or if the temperature might drop is this level within 4 hrs of applications
- ◆ Do not over-thin or over-extend the brush
- ◆ Stir well and strain before use
- ◆ Tinted paints need thorough shaking immediately after stainer addition as well as before use
- ♦ Store the container with the lid tightly closed in an upright position in a cool dry place
- Keep out of reach of children and away from eatables
- ♦ May be harmful if swallowed. In case of ingestion seek immediate medical attention
- ♦ Wear eye protection during application in case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- ♦ In case of skin contact immediately wash skin with soap and plenty of water Get medical attention if irritation develops or persists.
- ◆ Do not breathe vapor or spray It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- ◆ Do not pour leftover paint down the drain or in water courses.
- ♦ In the event of spills, contain spillage using sand or earth
- ♦ No added Lead. Mercury or Chromium compounds.

### **AQUA PAINTS & CHEMICALS**

# 214 & 215, JCK Industrial Park, Belagola Industrial Area KRS Cross Road, Metagalli, Mysuru-570016





